



## Switches

	<p><b>PFS3005-4P-58</b>  <b>PoE 4-portni switch</b>; 1x 10/100 Base-T; 4x 10/100 Base-T (PoE); <b>Do 30W po portu ili maksimalno 58W ukupno(za sve portove)</b>; PoE protokol IEEE802.3af i IEEE802.3at; MAC auto study and aging, Broj MAC adresa 1K; Default i Extended mod rada.Default je kao standarni switch,dok se u Extended modu PoE portovi se ponašaju kao 10Mbps portovi sa dometom do 250m ; Napajanje DC51V priloženo uz uređaj; Radna temperatura od 10°C~50°C; Dimenzije 100mm×100mm×26mm; Masa uređaja 259g</p>	50,00	60,00
	<p><b>PFS3005-5GT-L</b>  <b>5 ports 10/100/1000Mbps</b></p>	13,00	15,60
	<p><b>PFS3005-4ET-60-V2</b>  4 portni POE neupravljivi svic, podrzava POE power management, podrzava 4 POE porta 10/100Mbps + 1 uplink port 100 Mbps</p>	54,00	64,80
	<p><b>PFS3006-4GT-60</b>  <b>6 portni (4POE)</b>, neupravljivi gigabitni svic, 1 port podrzava HI-POE (60W), podrzava 4 POE porta 10/100/1000 Mbps + 2 uplink porta 10/100/1000 Mbps</p>	76,00	91,20
	<p><b>PFS3110-8ET-96</b>  <b>PoE 8-portni switch industrijski</b>; 1x100/1000 Base-x ;1x10/100/1000 Base-T; 8x10/100 Base-T (PoE);  <b>Do 30w po portu ili maksimalno 96w (ukupno za sve portove) poebno podesavanje potrosnje za svaki port</b>; PoE protokol IEEE 802.3afi IEEE 802.3at;, Broj MAC adresa 8K; Napajanje DC53V prilozeno uz uređaj; Radna temperatura od -30°C do 65°C; Dimenzije 150mm×100mm×42mm; Masa uređaja 540g  Podrzava sledece SFP module:  PFT3950 1.25G 850nm,500m,LC, Multi-mode  PFT3960 1.25G 1310/1550nm,20km,LC, Single-mode  PFT3970 1.25G 1550/1310nm,20km,LC, Single-mode</p>	143,00	171,60
	<p><b>PFS3010-8GT-96</b>  10-portni gigabitni neupravljivi svic, 8 POE portova, podrzava IEEE802.3bt I HI POE standarde, maksimalna snaga je 90W po portu.</p>	149,00	178,80

	<p><b>PFS3009-8ET-96</b>  <b>Poe 8-portni switch</b>, 1x10/100 Base-T, 8x10/100,  Do 60W po portu maksimalno potr 1. PoE protokol  IEEE802.3af i IEEE802. Dimenzije  190mm×100mm×30mm. Radna temperatura -  10°C~+55°C. Napajanje DC48~57V power adapter.</p>	86,00	103,20
	<p><b>PFS3008-8GT-60</b>  8-portni gigabitni PoE switch 8 x10/100/1000M Base-  T (PoE power supply)  4x 10/100/1000M Base-T (PoE power supply)  4x 10/100/1000M Base-T; Port1≤60W, Port2-  4≤30W, Total≤60W IEEE802.3af/IEEE802.3at/Hi-  PoE Power supply:DC48~57V  Dimenzije: 190mm×100mm×30mm  Masa: 480g</p>	60,00	72,00
	<p><b>PFS3008-8GT-96</b>  <b>8-portni gigabitni PoE switch</b> 8 x10/100/1000M  Base-T (PoE power supply)  Port1≤60W, Port2-8≤30W, Total≤96W  IEEE802.3af/IEEE802.3at/Hi-PoE  Power supply:DC48~57V  Dimenzije: 190mm×100mm×30mm  Masa: 480g  Podrjava sledece SFP module:  PFT3950 1.25G 850nm,500m,LC, Multi-mode  PFT3960 1.25G 1310/1550nm,20km,LC, Single-  mode  PFT3970 1.25G 1550/1310nm,20km,LC, Single-  mode</p>	108,00	129,60
	<p><b>PFS3008-8GT-L</b>  <b>8 ports 10/100/1000Mbps</b></p>	16,00	19,20
	<p><b>PFS3008-8GT</b>  8-Port Unmanaged Desktop Gigabit Switch, Layer 2  unmanaged access switch, All gigabit ethernet ports  Lightning protection, Plug and play, Adopts metal  enclosure, Good heat dissipation</p>	22,00	26,40
	<p><b>PFS3009-8ET1GT-96</b>  Unmanaged Desktop Svitc sa 8 Port PoE  Intelligentni PoE  BT 90V  8-pin dodeljivanje PoE napajanja  PoE na daljinu  PoE čuvar  Široka radna temperatura</p>	65,00	78,00
	<p><b>PFS4018-16P-250</b>  16-portni upravljivi POE switch, 2*10/100/1000  Base-T  16*10/100 Base-T(PoE power supply), ukupan POE  budyet 250W,</p>	488,00	585,60
	<p><b>PFS4218-16ET-240</b>  Upravljivi svic sa 16 x 100mbps POE portova i 2 x  gigabit POE porta, inteligent POE, 240W ukupno,  250m POE distanca, POE watchdog, plug&amp;play,</p>	363,00	435,60

	<p><b>PFS4218-16ET-190</b>  <b>16-portni PoE switch</b>; 2x10/100/1000 Base-T (Combo); 2x1000 Base-X (Combo); 16x10/100 Base-T (PoE);  <b>Do 60W po portu ili maksimalno 190W (Ukupno za sve kanale)</b> ; PoE protokol IEEE 802.3af, IEEE 802.3ati Hi PoE; Switching Capacity 8.8G; Packet Forwarding Rate 6.66 Mpps; Spanning tree protocol STP/RSTP; Napajanje 220V Ac; Radna temperatura od -10°C do 55°C; Dimenzije 440mmx300mmx44mm; Masa 3.51g  Podrjava sledece SFP module:  PFT3950 1.25G 850nm,500m,LC, Multi-mode  PFT3960 1.25G 1310/1550nm,20km,LC, Single-mode  PFT3970 1.25G 1550/1310nm,20km,LC, Single-mode</p>	273,00	327,60
	<p><b>DH-PFS3226-24ET-240</b>  Neupravljivi switch sa 24 POE porta, dual port uplink 100mbps, plug &amp; play, HI-POE, optimalna radna distanca 250m.</p>	294,00	352,80
	<p><b>PFS3228-24GT-360</b>  Neupravljani PoE switch sa crvenim portom podrjava standard IEEE802.3bt. Podrjava maksimalnu snagu od 90V Oobezbeduje stabilan rad u ekstremnim uslovima. Gigabitni pristupi odrzavaju visoku brzinu. Gigabit uplink optičko vlakno podrjava dug prenos na daljinu.  - Intelligent PoE  · Crveni port podrjava BT 90V  · Svi giga- portovi  · Glatki prenos  · Široka radna temperatura: -10°C do 55°C (14°F do 131°F)  · Plug and Play</p>	498,00	597,60
	<p><b>PFS4226-24ET-240</b>  24 portni industrijski POE switch  2*10/100/1000 Base-T (Combo port), 2*1000 Base-X (Combo port), 24*10/100 Base-T (PoE napajanje), svaki izlaz ≤30W, Ukupno ≤360W, Port 1/2 podrjava Hi-PoE (60W), PoE+, PoE, PoE protokol: IEEE802.3af, IEEE802.3at, Hi-PoE, PoE transmisija do 250m, Radna temperatura: -10°C~55°C, Dimenzije:440mm×300mm×44mm  Podrjava sledece SFP module:  PFT3950 1.25G 850nm,500m,LC, Multi-mode  PFT3960 1.25G 1310/1550nm,20km,LC, Single-mode  PFT3970 1.25G 1550/1310nm,20km,LC, Single-mode</p>	344,00	412,80

	<p><b>PFS4226-24ET-360</b>  24 portni industrijski POE switch  2*10/100/1000 Base-T (Combo port), 2*1000 Base-X (Combo port), 24*10/100 Base-T (PoE napajanje), svaki izlaz ≤30W, Ukupno ≤360W, Port 1/2 podržava Hi-PoE (60W), PoE+, PoE, PoE protokol: IEEE802.3af, IEEE802.3at, Hi-PoE, PoE transmisija do 250m, Radna temperatura: -10°C~55°C, Dimenzije:440mm×300mm×44mm  Podržava sledece SFP module:  PFT3950 1.25G 850nm,500m,LC, Multi-mode  PFT3960 1.25G 1310/1550nm,20km,LC, Single-mode  PFT3970 1.25G 1550/1310nm,20km,LC, Single-mode</p>	446,00	535,20
	PFT3950 1.25G 850nm,500m,LC, Multi-mode	48,00	57,60
	PFT3960 1.25G 1310/1550nm,20km,LC, Single-mode	50,00	60,00
	PFT3970 1.25G 1550/1310nm,20km,LC, Single-mode	76,00	91,20